

Product	Strongweld 132 GAS NO GAS - 130 Amp Mig/Flux-Cored Wire Feed		
Description	Single-phase portable MIG welding units with cooling fan. Polarity can be reversed to weld using cored wire without shielding gas. Equipped with torch, earth cable, cored wire spool. Well suited to weld without shielding gas and pressure reducer. The reel holder accepts spools from 2 to 11 pounds		
Product Code	1025132 - 99405007	Country of Origin	Italy



2 Year Warranty!

**120V 50-60Hz
40-130 Amp**

Made in Europe



Also available in red

General Specifications

Input Power	120V - 15A Plug (Fuse)	Output Range	40-130 Amp
Rated Output	90A@20%	Welding Position Adjustment	4 positions

Welding Cables

Input Cable	3XAWG14 8ft with 15A plug	Mig Gun	Fix Torch - Gauge 7 - 7ft - Gas/No Gas - Tweco 1 consumables
Ground Cable	Gauge 7 - 6.5ft		

Accessories Included

Contact Tips Diameters 0,024-0,030-0,035 / Flux Cored Wire spool diameter 0,035" - 1lb / Solid Wire spool diameter 0,030" - 1lb Chipper Hammer / Wire Brush / Hand Shield

Dimension & Weight

Unit Dimensions (L-W-H, inches)	19.7	9.8	15.7	Net Weight	55lb
Box Dimensions (L-W-H, inches)	22.2	12.6	16.5	Gross Weight	58lb

Welding Parameters

Model Type	GMAW/FCAW Portable Welder with Wire Feeder				
Input	1 phase	120V	60Hz	13A	CSA Rated Output
Rated Output	40A-130A				
Amperage	125A	90A	50A	40A	60A
Volts	16V	16V	16V	15.5V	21V
Duty Cycle	10%	20%	60%	100%	40%
Max OCV	30VDC				30VDC

Notes: In some countries marketed as Panther 132 or Amigo 132

360 Grand Cypress Ave - 301, Palmdale, CA 93551
661-274-0584 / www.strongweld.net / info@strongweld.net